



TECHNICAL SPECIFICATIONS

TEMPERATURE -20,0 °C à 35,0 °C
-4,0 °F à 194,0 °F

PRESSURE Up to 20 bar
Up to 290 psi

SPEED Up to 15 m/s
Up to 2950 ft/m

FEATURES Balanced
Suitable for high-pressure applications
Cartridge O-ring type seal

STATIONNARY SEAT included

MATERIALS

ROTATIVE FACE Silicon Carbide

ELASTOMER FKM

METAL PARTS Stainless Steel

SPRING Stainless Steel

STATIONNARY FACE Silicon Carbide

	D1	L1	D3	M
12mm	12,0	55,0	29,0	M28x1,5
16mm	16,0	57,5	34,0	M35x1,5
22mm	22,0	71,0	50,0	

PUMP MODELS

	12mm	16mm	22mm
CR	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
CR8	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
CRI	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
CRN1, CRN3, CRN5	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
CRN10, CRN15, CRN20	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
CRN32, CRN45, CRN64	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
CRN90	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
CRNE1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
CRNE2-23HS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>